CAD CUT

OS PU FOAM

O-SUNG C&T CO., LTD

DESCRIPTION

OS PU FOAM is high thickness(750 microns) film based on PU material.

Despite the outstanding thickness, it allows easy cutting, weeding and application.

SPECIFICATION

- Non-adhesive type
- Adapted to cotton, polyester, fashion industry and etc...]
- Thick PU film based in polyurethane material
- Recommended to press 2 times

TECHNICAL DATA

Transfer Film :	**Polyurethane**
Adhesive :	**Polyester Hotmelt**
Liner :	**PET**
Thickness :	**750 microns [±10]**

PACKING & STORAGE

- 50cm x 15m (per roll)
- Use the film within 1 year from manufacturing day
- It is recommended to stay away from direct sunlight, hot and humid place

APPLICATION

Temperature :	**160℃ - 310℉**
Time :	**5 sec.**
	(2 times - Front, Back)
Liner removal :	**Hot**

SETTING & WASHING

- **Medium Pressure**
- **Blade 45˚**
- **Wash resistance :** **Max at 80˚**

* All data is just examples based on our experience and not guaranteed performance.
* If the working environment or method is not typical, we recommend you to consult us in advance.

O-SUNG C&T CO., LTD

HEADQUARTERS

465, Gonghang-daero, Gangseo-gu, Seoul, KOREA

http://www.ostco.com

TEL: +82 2 3664 5577 [REP]

FAX: +82 2 3665 4789

email: export@ostco.com