

OS 300 NYLON COMPRINTER

DESCRIPTION

Nylon comprinter film gives a very thin feeling and is light and soft with strong elasticity and excellent ability for cutting fine letters.

This film which is made of polyamide material allows you to make any difficult designs. With its strong workability, you can easily cut and weed small logos or drawings.

Ink Types: solvent inks, mild solvent inks and eco solvent



SPECIFICATION

- Adhesive type
- Adapted to cotton, polyester, sweat suit, wind breakers, tent, umbrella, etc...
- Before washing, turn garment inside out
- Machine wash only

PACKING & STORAGE

- 50cm x 50m (per roll)
- Use the film within 1 year from manufacturing day
- It is recommended to stay away from direct sunlight, hot and humid place

TECHNICAL DATA

Transfer Film :	Nylon
Adhesive :	Polyamide Hotmelt
Liner :	PET
 Thickness :	80 microns [± 10]

APPLICATION

 Temperature :	150°C - 300°F
 Time :	7 to 8 sec.
 Liner removal :	Hot
Transfer Tape :	OS-MASK TACK OS-MEDIUM MASK TACK

SETTING & WASHING

- Medium Pressure
- Blade 45°
- Wash resistance : Max at 80°

* All data is just examples based on our experience and not guaranteed performance.

* If the working environment or method is not typical, we recommend you to consult us in advance.

O-SUNG C&T CO., LTD

HEADQUARTERS

465, Gonghang-daero, Gangseo-gu, Seoul, KOREA

<http://www.ostco.com>

TEL: +82 2 3664 5577 [REP]

FAX: +82 2 3665 4789

email: export@ostco.com