



DESCRIPTION

OS FOAM COMPRINTER film is print & cut media film with high thickness (600 microns) based on PU material.

It provides a soft, raised texture that enhances design depth and visual impact.

Ink Types: solvent inks, mild solvent inks and eco solvent



SPECIFICATION

- Adhesive type
- Adapted to cotton, polyester, fashion industry and etc...]
- Thick PU film based in polyurethane material

TECHNICAL DATA

Transfer Film :	Polyurethane
Adhesive :	Polyester Hotmelt
Liner :	PET
Thickness :	600 microns [± 10]

APPLICATION

Temperature :	160°C - 320°F
Time :	7 sec

Liner removal :	Hot
Transfer Tape :	OS-MASK TACK OS-MEDIUM MASK TACK

PACKING & STORAGE

- 50cm x 25m (per roll)
- Use the film within 1 year from manufacturing day
- It is recommended to stay away from direct sunlight, hot and humid place

SETTING & WASHING

- Medium Pressure
- Wash resistance : Max at 80°

* All data is just examples based on our experience and not guaranteed performance.
* If the working environment or method is not typical, we recommend you to consult us in advance.

O-SUNG C&T CO., LTD

HEADQUARTERS

465, Gonghang-daero, Gangseo-gu, Seoul, KOREA

<http://www.ostco.com>

TEL: +82 2 3664 5577 [REP]

FAX: +82 2 3665 4789

email: export@ostco.com