O-SUNG C&T CO.,LTD.

TECHNICAL DATA

	Product Name	Base	Hotmelt	Thickness	Weight	Peel type		Technical Info.			Matte Finishing	Glossy Finishing	Opaque	Transparent	Adhesive Liner	Core	width	Length
				(㎛ ±5%)	(kg/roll)	Cool	Hot	Temp (℃ ±5%)	Time (± 2 sec)	Washing (Max ℃)							(m)	(m)
Printing Film	OS100-PVC Comprinter	PVC	Polyester	160	10.5		O	155	7.5	80	O	O	O			3"	0.50	50.00
	OS200-PU Comprinter	PVC	PU	70	8		O	145	7.5	80	O	O	O		O	3"	0.50	50.00
	OS300-Nylon Comprinter	PU	Polyamide	70	8		O	145	7.5	80	O	O	O			3"	0.50	50.00
	OS500-PU Clear Comprinter	PVC	PU	70	8		O	145	7.5	80	O			O	O	3"	0.50	50.00
	OS700-PS Comprinter	PU	Polyester	85	8		O	145	7.5	60	O	O	O		O	3"	0.50	50.00
	OS710-NEW PS Comprinter	NYLON	Polyester	85	8		O	145	7.5	60	O	O	O		O	3"	0.49	100.00
	OS-PS Clear Comprinter	PU	Polyester	85	8		O	145	7.5	60	O			O	O	3"	0.50	25.00
	OS-Gold/Silver Comprinter	PU	Polyester	80	8		O	145	7.5	60	O		O		O	3"	0.50	50.00
	OS-ECO SOL Comprinter	PU	Polyester	70	8		O	145	7.5	60	O		O		O	3"	0.50	50.00
	OS-LATEX Comprinter	PU	Polyester	60	8		O	145	7.5	60	O		O			3"	0.50	50.00
	OS-Glow In the dark Comprinter	PU	Polyester	90	11		O	145	7.5	60	O		O		O	3"	0.50	15.00
	OS-Sub Comrpinter (SUB BLOCK)	PU	Polyester	90	11		O	145	7.5	80	O		O		O	3"	0.50	50.00
	OS-Clear/Gold Comprinter	PU	Polyester	80	8		O	145	7.5	60	O		O		O	3"	0.50	50.00
	OS-Pearl Comprinter	PU	Polyester	85	8		O	145	7.5	60	O		O		O	3"	0.50	50.00
	OS-UV Comprinter	PU	Polyester	90	9		O	145	7.5	60	O		O		O	3"	0.50	50.00